



NOTES:

- ① HIGH DENSITY POLYETHYLENE ADJUSTING RINGS SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS STARTING ON A SOLID, CLEANED TOP SECTION OF THE INPLACE CATCH BASIN. THE CATCH BASIN FRAME & RING CASTING SHALL BE SEALED TO THE STRUCTURE WITH A UNI-BAND (RUBBER) SEALING SYSTEM.
- ② FOR 2X3 BOXES, UNIBANDS SHALL EXTEND ONTO THE VERTICAL PORTION OF THE STRUCTURE. FOR MH-CB'S, UNIBAND SHALL BE MODIFIED TO SEAL TO TOP SLAB OF THE STRUCTURE. MULTIPLE UNIBANDS MAY BE NEEDED.
- ③ REFER TO PLANS AND/OR SPECIAL PROVISIONS FOR FRAME AND GRATE TYPE.
- ④ 0.33' - DESIGN D4 MODIFIED C&G  
0.50' - DESIGN B618 OR B624 C&G
- ⑤ 2'x3' BOX OR 2'x3' OPENING IN COVER SLAB
6. FOR ADJUSTMENTS IN DESIGN B624 C&G 6" OF CONCRETE SHALL BE PLACED FRONTING THE FRONT EDGE OF THE FRAME.

DATE REVISED  
03/20/19

2'x3' CB FRAME ADJUSTMENT

PLATE NO.  
1-01